

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## **IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
Please do not report the images to the  
Image Problem Mailbox.

REMARKS

Reconsideration of the above-identified application in view of the following remarks is respectfully requested.

A Substitute Specification and associated marked-up copy of it have been submitted with this Amendment for the Examiner's approval. **No new matter has been added by this Substitute Specification.**

A proposed Drawing Amendment in accordance with the Substitute Specification has been attached to this Amendment for the Examiner's approval. Formal Drawings in accordance with the proposed Drawing Amendment have also been submitted with this Amendment.

Claims 1-56 have been rejected as indefinite. Claims 36-56 have been rejected as being directed to non-statutory subject matter. The claims have been amended to overcome these rejections.

Claims 1, 22, and 36 have been rejected under the doctrine of non-statutory double patenting. This rejection has been overcome by the concurrently submitted Terminal Disclaimer.

Claims 1-4, 22-24, and 36-39 have been rejected as anticipated by Lee et al., US 6,263,358. Claims 5-21, 25-26, and 40-56 have been rejected as unpatentable over Lee et al.

The limitations of claims 5, 26, and 40 have been added to independent claims 1, 22, and 36. Claims 5, 26, and 40 have been canceled without prejudice.

In rejecting claims 5, 26, and 40 as obvious over Lee et al., the Office Action stated the following:

Lee does not specifically teach wherein said graph is a PN graph and said representation is a PN representation and each agent calculates deadlock avoidance structures relating to said PN representation and graph. Lee does teach the use of coordination graphs (col. 9, line 34; cols. 38-40) and GANTT chart type presentations (col. 34, lines 18-25) to avoid undesired behaviors such as deadlock (col. 32, lines 57-65). It would have been obvious to one of ordinary skill in the art to include the PN graph and the PN representation, because it is widely used to model discrete systems and provides for ease of analysis and design by facilitating the mapping of tasks.

(See Office Action, pages 8-9).

It appears that the position of the Office Action is that it would have been obvious to program the coordination engine (210) of Lee et al. to calculate deadlock avoidance structures relating to an internal representation of initialization data and a graph, as recited in claims 5, 26, and 40, even though Lee et al. does not teach these features.

The M.P.E.P. sets forth the following criteria for an obviousness rejection under 35 U.S.C. §103:

To establish a prima facie case of obviousness, three basic criteria must be met. First, there must be some suggestion or motivation, either in the references themselves or in the knowledge generally available to one of ordinary skill in the art, to modify the reference or to combine reference teachings. Second, there must be a reasonable expectation of success. Finally, the prior art reference (or references when combined) must teach or suggest all the claim limitations.

See, MPEP §706.02(j).

The structure of a computer programmed to carry out an algorithm is limited by the disclosed algorithm. See WMS Gaming Inc. v. Int'l Game Tech., 184 F.3d 1339, 1348 (Fed. Cir. 1999). A new machine (a special purpose computer) is

created when a general purpose computer is programmed to carry out an algorithm for performing one or more particular functions. Id. citing In Re Alappat, 33 F.3d 1526, 1545 (Fed. Cir. 1994) (*en banc*). When a general purpose computer is programmed to perform a particular function by using a discovery not specified in the prior art, the resulting device would not be obvious under 35 U.S.C. §103 "because one not having knowledge of the [inventor's] discovery simply would not know what to program the computer to do." See In re Prater, 415 F.2d 1393, 1397-98 (CCPA 1969).

For an obviousness rejection under 35 U.S.C. §103, the prior art must be analyzed at the time the invention was made. The use of the teachings of the present invention to find obviousness is impermissible.

Obviousness must not be read into an invention on the basis of applicant's own statements; that is, the prior art must be viewed without reading into that art the applicant's teachings. The issue, then, is whether the teachings of the prior art would, in and of themselves and without the benefits of appellant's disclosure, make the invention obvious.

In Re Spinnoble, 160 USPQ 237, 243 (CCPA 1969) (emphasis in original). Accordingly, the Examiner must consider only the teachings of the prior art references.

As admitted in the Office Action, Lee et al. fails to teach or suggest the calculating of deadlock avoidance structures relating to an internal representation of initialization data and a first graph. (Office Action, pages 8-9). Therefore, it is clear that the features of claims 5, 26, and 40 (amended claims 1, 22, and 36) are not taught by Lee et al. According to WMS Gaming Inc., 184 F.3d at 1348,

the structure of the first agent computer of the present invention is the algorithm for calculating deadlock avoidance structures relating to an internal representation of initialization data and the first graph. Since Lee et al. admittedly fails to teach or suggest these features, Lee et al. fails to teach or suggest a computer having the structure of the first agent computer of claims 1, 22, and 36. Since Lee et al. fails to teach or suggest each feature of the claimed invention, it is respectfully submitted that the invention of amended claims 1, 22, and 36 would not have been obvious to one of ordinary skill in the art.

Additionally, when an algorithm is not taught or suggested by the prior art, one of ordinary skill in the art would not know what to program a computer to do. See e.g., In re Prater, 415 F.2d at 1397-98. Thus, a new machine has been created when a general purpose computer is programmed to carry out an algorithm to perform a particular function, as in claims 1, 22, and 36. WMS Gaming Inc., 184 F.3d at 1348. Therefore, it is respectfully submitted that it would not have been obvious for one of ordinary skill in the art to program the coordination engine (210) of Lee et al. to calculate deadlock avoidance structures relating to an internal representation of initialization data and the first graph. Thus, it is respectfully submitted that the rejection of claims 5, 26, and 40 (amended claims 1, 22, and 36) as obvious over Lee et al. is improper.

Furthermore, in rejecting claims 5, 26, and 40 as obvious over Lee et al., it is respectfully suggested that improper

hindsight has been used. The prior art fails to teach or suggest calculating deadlock avoidance structures relating to an internal representation of initialization data and the first graph. Thus, without reference to the teachings of the disclosure of the present invention, one of ordinary skill in the art would not have the requisite knowledge to calculate deadlock avoidance structures relating to an internal representation of initialization data and the first graph, as recited in amended claims 1, 22, and 36.

According to In Re Sponnoble, 160 USPQ at 243 (CCPA 1969), such hindsight is impermissible. Therefore, it is respectfully submitted that for this further reason, the rejection of claims 5, 26, and 40 is improper.


Claim 1, as well as claims 2-4 and 6-21 which depend from claim 1, are in condition for allowance. Claim 22, as well as claims 23-25 and 27-35 which depend from claim 22, are in condition for allowance. Claim 36, as well as claims 37-39 and 41-56 which depend from claim 36, are in condition for allowance.

Allowance of the subject application is respectfully requested.

Serial No. 09/740,544

Please charge any deficiency or credit any overpayment in  
the fees for this election to our Deposit Account No. 20-0090.

Respectfully submitted,

  
Robert N. Lipcsik  
Reg. No. 44,460

TAROLLI, SUNDHEIM, COVELL,  
& TUMMINO, LLP  
526 Superior Avenue - Suite 1111  
Cleveland, Ohio 44114-1400  
Phone: (216) 621-2234  
Fax: (216) 621-4072  
Customer No. 26294



PATENT

RECEIVED

MAY 13 2004

Technology Center 2100

**APPARATUS AND METHOD FOR RESOURCE  
NEGOTIATIONS AMONG AUTONOMOUS AGENTS**

**Background of the Invention**

**Technical Field**

- 5           The present invention relates to apparatus and method for  
controlling allocation of resources among autonomous agents that  
negotiate for the resources.

**Description of Related Art**

- The problems of resource negotiation, allocation, and general  
10       logistics are applicable to most industries. These include the military,  
manufacturers, and trading and commerce organizations.

- Frequently, real world applications involve the actions of multiple  
(semi-) autonomous units or teams, engaged in tasks directed toward the  
achievement of common goals, sharing a limited supply of essential  
15       resources, and operating in a dynamic, changing environment. Members  
of teams include computers, other cooperating agents or people operating



computers. Each member of a team has resources that may be required to complete tasks and/or has the ability to execute tasks given the necessary resources. Logistics is a prime example of one such application, but examples also include process control and flexible manufacturing in industry, commerce and quality in economics, and autonomous control and distributed robotics in engineering research. Algorithms from operations research and auction-based negotiation schemes have been developed for automating the solution to resource allocation problems. However, these methods are generally written as centralized procedures. It is necessary to disseminate the results to the actual players, making it difficult to account for unforeseen elements in the operating environment or to respond to changing conditions. Furthermore, centralized solutions to resource allocation problems do not always scale well, they may be impractical due to processing or memory constraints, depending on the size of the problem. Simple distributed negotiation techniques exist for solving resource allocation problems. However what these techniques make up for in terms of dynamic operation and processing requirements, they lack in terms of the overall quality of the solution. Failure of a central resource may defeat the process. Bidding may be purely competitive rather than attempting to optimize use of resources versus performance demands. Finally, both distributed and centralized methods lack an inherent mechanism for representing task flow or the complex relationships and inter-dependencies between tasks and

between tasks and resources. Their architecture ~~model~~ does not include task flow, as well as who gets what resource.

### Summary of the Invention

An architecture is presented herein for pseudo-centralized planning and resource allocation among distributed units incorporated with  
 5 complete, formal representations of task flow, constraints, and interdependency. The technique is referred to as pseudo-centralization because it involves the parallelization of centralized solutions so that they ~~can~~ <sup>may</sup> be implemented by discrete, spatially distributed processors. The distributed nature of the solution permits units to respond to unforeseen or  
 10 changing situations as they occur.

Negotiation among units makes use of auction-based algorithms. One advantage of these methods is that they are highly parallelizable, and may be implemented by semi-independent computations on processors at each supplier and consumer entity. So long as search processor bids  
 15 according to the same algorithm and the same relative value for price and cost, based on norms and instructions from higher authority, they need only exchange bids for the system to work. Pseudo-centralized planning results, where the use of physically distributed agents employing communications to negotiate according to the rules of the more centralized  
 20 auction algorithms will provide the coordination and performance benefits of centralization with the speed and robustness of distributed processing.

Each functioning unit of the solution is a resource holder and/or a task executor. These units are described by Petri net discrete event

system models. The richness of these models incorporates task flow, physical and logical constraints, resource usage, and the interdependencies among tasks and resources. Petri nets incorporate the conflicts, synchronization, and concurrencies that are essential elements of a sophisticated architecture for distributed resource and mission planning problems.

An architecture is presented for decentralizing resource allocation and negotiation algorithms, allowing them to be implemented by spatially-distributed processors with limited communications. The architecture also supports a flexible, formal representation of task-flow and interdependency that is missing from other methods, centralized or distributed, designed to tackle these problems. A scalable, distributed network of modular team task descriptions and resource dependencies is created and managed in real time. The scalability and distributed nature of the architecture allows the network to be dynamically modified as tasks are accomplished, goals shift, and new environmental conditions are encountered. The architecture has a wide range of applications in the areas of logistics, flexible manufacturing, process control, autonomous distributed robotics, economics, or any area in which resources are produced and consumed in the goal-directed execution of tasks.

As discussed above, resource allocation problems have been automated using techniques from operations research, such as linear programming, and centralized auction-based negotiation schemes. Task

flow and resource dependencies have been modeled <sup>with</sup> ~~with~~ Petri nets, among other formalisms, <sup>However</sup> ~~however~~ these systems are generally not distributed and they are not equipped with the algorithms that negotiate ~~for~~ and allocate resources to solve those tasks.

5

### ~~Summary of the Invention~~

It is therefore a general object of the present invention to provide an architecture and method for decentralizing resource allocation and negotiation algorithms, allowing them to be implemented by spatially-distributed processors with limited communications.

10

It is also an object of the present invention to provide an architecture and method of the type described that also supports a flexible, formal representation of task-flow and interdependency that is missing <sup>from</sup> ~~from~~ other methods, centralized or distributed, designed to tackle these problems.

15

It is a more specific object of the present invention to provide a method and apparatus of the type described <sup>to</sup> ~~in one~~ form a scalable, distributed network of modular team task descriptions and resource dependencies that is created and managed in real time.

20

It is an additional object of the present invention to provide an architecture and method of the type described in which the scalability and distributed nature of the architecture allows the network to be dynamically modified as tasks are accomplished, goals shift, and new environmental conditions are encountered.

It is a further general object of the present invention to provide an architecture and method of the type described in which the architecture has a wide range of applications in the areas of logistics, flexible manufacturing, process control, autonomous distributed robotics, economics, or any area in which resources are produced and consumed in the goal-directed execution of tasks.

One aspect of the invention supports a scalable architecture, permitting centralized negotiation procedures to be handled by distributed units. This decreases the processing and memory requirements for individual systems, and is necessary for a resource allocation solution in which it is impossible or impractical for a central authority to continuously communicate with its acting units.

Another aspect of the invention provides the use of Petri nets that permit an explicit description of task flow and interdependency. Modeling task flow as well as the allocation of resources makes the architecture better suited to handle dynamic changes in the environment or the nature of the problem. Finally, an implementation of completely autonomous units requires an architecture such as that disclosed, i.e., it supports resource negotiation, allocation, constraints, task flow, and interdependency among all of these elements.

In accordance with the present invention, a distributed data processing system is provided which employs negotiation among autonomous agents for allocation of resources. The system includes a

communications network for passing messages between computers connected thereto. A plurality of computers are connected to the network for running programs thereon including at least first and second autonomous agents. Each agent receives a graph associated therewith  
5 and wherein the graph represents for the associated agent what resources that agent has and what task or tasks that agent may perform. Each agent employs the associated graph to determine what resource or resources are needed by that agent to carry out the tasks to be performed by that agent. The agents negotiate with each other for the resources needed to carry out  
10 the tasks to be performed by the agents.

In accordance with another aspect of the present invention, a method is provided and wherein the method is operative in a distributed data processing system employing negotiation between autonomous agents for allocation of resources. The method employs a communication  
15 network for passing messages between computers connected thereto and wherein the computers are operative to run programs thereon including a central authority and at least first and second autonomous agents. The method includes the steps of each agent receiving a graph associated therewith and representing for that agent what resources that agent has  
20 and what task or tasks that agent may use the resources ~~for~~. Each agent employs the associated graph for determining what resource or resources are needed by that agent to carry out the task or tasks performed by that

agent. The agents negotiate with each other for the resources needed to carry out the task <sup>or</sup> ~~to~~ tasks to be performed by the agents.

In accordance with a still further aspect of the present invention a computer program product operative in a system as set forth above is  
5 provided and wherein the product includes at least first and second autonomous agents.

### **Brief Description of the Drawings**

The foregoing and other advantages of the invention will become more readily apparent from the following description of a preferred  
10 embodiment of the invention as taken in conjunction with the accompanying drawings, which are a part hereof, and wherein:

Fig. 1 is an illustration showing high level architecture and algorithm flow involved in the invention herein;

Fig. 2 is a flow diagram illustrating a portion of the invention herein;

15 Fig. 3 which is comprised of Figs. 3A and 3B illustrate Petri Net (PN) representing resource-using tasks useful in describing the invention herein;

Fig. 4 which is comprised of Figs. 4A and 4B illustrates more detailed PN graphs useful in describing the invention herein;

Fig. 5 illustrates a still further PN graph useful in describing the  
20 invention herein;

Fig. 6 illustrates a network having central authority and agent machines connected thereto;

Fig. 7 is a graphical illustration indicative of the hardware employed in each of the computers connected to the network of Fig. 6;

Fig. 8 is a graphical illustration of the strategic layer-central authority showing various inputs and outputs;

5 Fig. 9 is a graphical illustration of the tactical layer-autonomous agents showing various inputs and outputs;

Fig. 10 is an overall illustration of the relationship and flow between the central authority and autonomous agents;

10 Fig. 11 is a flow diagram of Part 1 of the strategic layer-central authority;

Fig. 12. is a flow diagram illustrating Part 2 of the strategic layer-central authority;

Fig. 13 is a flow diagram illustrating Part 1 of the tactical layer-autonomous agents; and

15 Fig. 14 is a flow diagram illustrating Part 2 of the tactical layer-autonomous agents.

### *Example* Description of the Preferred Embodiments

An architecture is presented herein that supports autonomous planning, resource allocation, and task execution for teams of independent  
20 entities operating in dynamic, changing environments. A scalable, distributed network of modular team task descriptions and resource dependencies is created and managed in real time. Initially, teams are



composed of units possessing resource and/or potential task execution assets. Automatic synthesis techniques are employed to create feasible inter-team links of dependency among tasks and resources. This step provides a framework for goal-directed decision making and task planning  
5 by human-managed or cybernetic reasoning systems. New higher level cooperating teams arise as an emergent phenomenon of these processes. The scalability and distributed nature of the architecture allows the network to be dynamically modified as tasks are accomplished, goals shift, and new environmental conditions are encountered. The architecture has a wide  
10 range of applications in the areas of logistics, flexible manufacturing, process control, autonomous distributed robotics, economics, or any area in which resources are produced and consumed in the goal-directed execution of tasks.

## 1 Introduction

15 A great number of real world applications involve the actions of multiple (semi-) autonomous units or teams, engaged in tasks directed toward the achievement of common goals, sharing a limited supply of essential resources, and operating in a dynamic, changing environment. Logistics is a prime example of one such application, but examples also  
20 include process control and flexible manufacturing in industry, commerce and quality in economics, and autonomous control and distributed robotics in engineering research. At the highest level, these problems are generally

solved by hand based on human intuition and experience. Some algorithms and procedural techniques exist to help solve lower level components of the bigger problems. It is desired to present a technical architecture that, when implemented, would serve as a powerful aid for human decision makers or serve as the central nervous system of a completely autonomous collection of cybernetic decision makers, Autonomous Negotiating Teams (ANT). A complete, practical architecture for autonomous resource negotiations in dynamic environments should have the following properties:

- Scalable architecture and flexible algorithm set
- Robust coordination through unit-level negotiations
- Real-time reorganization in case of dynamic situation changes
- Insensitivity to loss of communications, local autonomy

An ANT architecture is presented herein that provides for these characteristics in a practical, achievable manner. ↩

The ANT architecture involves a unique set of diverse research areas combined to achieve both robustness to disruption of the command hierarchy and allocation efficiency superior to the current state of the art. It provides a distributed solution to resource allocation and hierarchical task execution problems. The resource allocation problem description, constraints, and objectives are broadcast to ANT processors in the field. Individual teams may perform certain tasks and/or hold resources needed for their own tasks or for the tasks of other teams. Using only limited two-

way communications, teams begin negotiating among themselves for the resources needed to complete their tasks. Links of dependency are dynamically created between teams, and supervisory control algorithms insure that these dependencies will not interfere with the completion of the objectives. Teams allocate and share resources, plan and execute tasks in accordance with the problem constraints and objectives. Unexpected changes in the environment or modified global directives will initiate dynamic recalculations and modifications to ANT behavior.

A solution is presented herein that partitions the environment and problem spaces and composes the tasks and processes within a dynamic, modular discrete event system framework. Resource allocation problems are solved using a combination of supervisory control, assignment algorithms, remote autonomous agents and pseudo-centralized planning.

Fig. 1 illustrates <sup>an example</sup> ~~the proposed~~ ANT system architecture. <sup>1001.</sup> Domain expertise and knowledge regarding the particular problem constraints and objectives are input at the start of the solution. Techniques from computational geometry and hierarchical clustering (~~see Section 2~~) are used to partition the problem space and assign resource costs and objective rewards. Knowledge representing task flow and resource requirements are composed as Petri net (PN) discrete event systems (~~see Section 2~~) and relayed to individual, possibly remote, ANT processors. Each ANT processor then accounts for its resource requirements by automatically augmenting its PN task description models using techniques

from supervisory control. This step includes an algorithm for deadlock avoidance to insure that the possible paths through the graph will not prohibit the completion of other crucial objectives.

Individual teams may have the knowledge or tools required to  
5 complete tasks or satisfy objectives without all of the necessary resources, or they may hold resources for which they have no immediate associated task. Remote autonomous agents (~~see Section 4~~) assigned to each team will then initiate local two-way communications to negotiate for the resources needed for task completion. This negotiation employs  
10 distributed implementations of computationally efficient assignment algorithms using the normalized costs and rewards provided by the environmental partitioner at the start of the algorithm. Requests for resources may be passed along chains of local communication to enable cooperation among isolated teams. Agreements reached through  
15 negotiations will result in the dynamic creation of new links of dependency throughout the distributed PN graph structure. Negotiations will employ pseudo-centralized planning making them capable of achieving superior results compared to completely localized negotiation schemes and making them less sensitive to interruptions in communication.

20 Once agreements have been finalized regarding the interdependency of resources and tasks, each team employs intelligent algorithms to search the PN graph for "good enough, fast enough" paths to the mission objectives. During mission execution, teams may experience

setbacks or become aware of changed environmental conditions. This information is used to initiate new resource negotiations and further modifications to the interdependent graph structure. Thus the teams dynamically respond to changing environments and continue to execute

5 their tasks and meet the mission objectives without interference from a centralized planner. The central planner may also make strategic decisions and initiate dynamic changes in the teams' behavior by broadcasting new tasks or simply by modifying the costs and rewards associated with resource consumption and objective completion. The

10 decisions of the central authority are strictly strategic: it is never required to micromanage the activities of the ANTs. All tactical decisions, including the details of negotiation, are left to the teams.

## 2 Environmental Partitioning and Composition of Tasks

Given a particular mission and objective, there are a number of

15 ~~critical~~ <sup>may be</sup> steps that ~~must be~~ performed before any autonomous negotiation between teammates can occur. An outline of these steps appears in Fig. 2. Obviously, different scenarios require different inputs, constraints, and task descriptions, though the underlying concepts are similar. <sup>Fig. 2</sup> ~~This~~

<sup>2nd</sup> ~~section~~ provides a general description of the components of ~~Fig. 2~~ that are

20 common to most scenarios.

## 2.1 Environmental Evaluation

The first set-up task is to accurately and efficiently evaluate the mission environment. <sup>2001.</sup> This consists of intelligently partitioning the environment locations in discrete regions representing different mission-dependent features. Different cost values are assigned to these areas, indicating a relative "cost" of traversing an area or a "reward" indicating the importance of accomplishing a partial mission objective. Any time, these features may be dependent on some sort of probabilistic or temporal function (e.g., a threat location may be known with a limited degree of certainty, or the desirability of a particular location may decrease after a specific duration). The architecture supports the constant introduction of new information, so information on the environment must be gathered and stored in such a way to make it easily accessible as well as easily modified in real-time. There are a number of unique data structures that aid in accurately partitioning the environment. [2, 11]

## 2.2 Parameterize Mission Objective and Constraints

Once the environment has been evaluated, the mission objectives and implied constraints <sup>may</sup> ~~must~~ be explicitly stated. <sup>2002.</sup> Various success criteria representing quantitative measures are applied to evaluate how close a unit or team is to completing the stated objectives.

### 2.3 Determination of Tasks/Resources and Dependencies


- Once the success criteria have been determined, the various tasks required to reach these objectives are defined. <sup>2003</sup> This is a difficult task; the ANT architecture tackles it with a "divide and conquer" approach. For each
- 5 mission scenario, a number of specific high-level tasks for ANT agents are defined as well as the specific resources (or resource combinations) that are required for each task. For these high-level task descriptions, detailed sub-tasks are defined to perform the higher-level tasks. Required and desired resources are associated with each of these tasks and sub-tasks.
- 10 A complete dependency list is then generated to link resources, tasks, and sub-tasks together.

### 2.4 Assign Penalties and Rewards

- Once the task (and subtask) dependencies and resources have been determined, relative penalties and rewards are assigned. <sup>2004.</sup> This is
- 15 required because any two tasks may require similar resources but may not be equally desirable when evaluating them against overall goals.

### 2.5 ANT Formation

- Low-level teams are formed to perform the tasks required to achieve mission goals. <sup>2005.</sup> Higher-level teams <sup>may</sup> dynamically emerge as the result of
- 20 autonomous negotiations, ~~see Section 4.7~~ Teams may be dynamically formed based on spatial locality or functionality (agents within the same geographic area, agents with similar duties or capabilities, or a combination

of these two). A number of different hierarchical structures may be used to represent the various teammates and associated command structure. 


After each of these critical tasks are performed, the ANTs are ready to begin dynamic negotiations for resources in the pursuit of mission

2006.  
5 objectives ~~as outlined in the following sections.~~

### ~~3 Discrete Event Systems and Supervisory Control~~

Discrete event systems (DES) are dynamic system models with state changes driven by the occurrence of individual events. DES may be used to provide a logical framework for handling the complex

10 interrelationship between resource allocation, resource consumption, and task-flow, and are thus an integral component of ANT architecture.

It is often necessary to regulate or supervise the behavior of these systems to include the constraints caused by a finite number of shared resources or to meet safety or performance criteria, e.g., insuring that  
15 resources are not allocated in such a way that it is impossible for any consumer to complete its given task. DES supervisors are used to insure that the behavior of the system does not violate a set of constraints under a variety of operating conditions. The regulatory actions of the supervisor are based on observations of the system state, resulting in feedback  
20 control. The process of preventing certain undesirable behaviors while otherwise allowing the system to evolve freely is known as supervisory control 



It is common to see DES modeled as finite automata. Methods exist for designing controllers based on automaton system models, however these methods often involve exhaustive searches or simulations of system behavior, making them impractical for systems with large numbers of states and transition causing events. One way of dealing with these problems is to model DES with Petri Nets.

### 3.1 The Petri Net DES Model

Petri nets (PN) [8] are a powerful and efficient DES model that incorporate the synchronization, conflict, and concurrency issues associated with the distributed, dynamic resource allocation problem of ANTs. They have a simple mathematical representation employing linear matrix algebra making them particularly useful for analysis and design. Fig. 3A shows an example of a PN model<sup>3001</sup> used to represent a sequence of states required to complete a task. Note that the final goal can be reached by using either resource 1 and 2 or resource 4, however resource 3 is required in both solutions.

PN's representing simple task flows may be composed to form high-level, hierarchical task descriptions. PN's facilitate a modular approach to the composition of processes. Hierarchical and inter-dependent relationships can easily be established starting with an initial set of simple but modular task descriptions. Fig. 3B shows a sample composition<sup>3002</sup>.

### 3.2 Supervisory Control

Often times the graphical representation of a system as a PN model is enough for an engineer to design a controller for the plant. Many control techniques exist that involve recognizing and then manipulating certain structures and situations that commonly appear in PN models. Other techniques exist for automatically verifying the reliability of these control designs. Representing the controller itself as a PN makes the verification of the combined plant/controller system simpler and reduces the number of computational tools required to model the overall system. Unfortunately, even when the controller is modeled as a PN, this cyclic technique of design and verification can become quite cumbersome when the domain model is large. ~~See [4] for a survey of some of the techniques used to control Petri net systems.~~ The ANT architecture employs automated techniques for synthesizing controllers based on the system model and constraint data.

Invariant based controllers ~~[7]~~ augment PN graphs with complex resource sharing constraints using scalable, computationally efficient calculations. <sup>Fig. 4(a)</sup> shows an example of two, potentially concurrent, tasks <sup>4001</sup>. Either task may make use of Resource 1 or 2. Constraints relating to the number of available finite resources are then added to the system. For example, there may be only one of each of Resources 1 and 2 available for the two missions. Using a PN supervisory control technique known as invariant based control, a mathematical representation of the resource

constraints is automatically converted into controlling PN structures using an extremely efficient linear matrix calculation. The emboldened places in Fig. 4a represent the supervisor that was synthesized using invariant based control. The tokens in these places represent the availability of a given finite resource. This automatic resource management technique can be used to model expendable resources like fuel and money, and reusable resources like equipment and manpower.

- Note that the model<sup>4001</sup> in Fig. 4a<sup>4001</sup> incorporates undesirable solutions, for example, Resource 1 may be allocated to Goal 1, while simultaneously Resource 2 is allocated to Goal 2. This situation will result in a local deadlock, i.e., two transitions within the PN become “dead.” This condition is avoided by the implementation of deadlock-avoidance/liveness-enforcement techniques. A solution<sup>4002</sup> to this problem is shown in Fig. 4b, the darkened places represent the new liveness-enforcing control structures.
- The solution<sup>4002</sup> was automatically synthesized using PN deadlock-avoidance algorithms from [7] and [5].

- Employing structural techniques for incorporating deadlock avoidance into the PN graph will automatically prune many infeasible solutions<sup>5000</sup> from the problem search space. Incorporating resource management and deadlock avoidance into the PN model provides a searchable graph that will not allow paths that lead to infeasible solutions. That is, an algorithm searching through states of the PN, looking for good resource allocation solutions, will not waste any of its time eliminating

paths that use too many resources or lead to deadlock. The PN graph structure and set of reachable PN states have already eliminated these infeasible solutions from the search.

*Table 1. Features of Negotiation Algorithms*

Algorithmic Feature	Advantage	Benefit
Auction-based	Highly parallelizable, and may be distributed	Supports autonomous team operations
Dynamic epsilon	Auction starts fast, then refines assignments	Rapid response to dynamic changes
JVC algorithm	Combines rapid start auction with modified Munkries for rapid finish	Real-time, high quality resource assignments
Lagrangian relaxation	Supports multidimensional assignment	Flexibly modifies initial assignments when needs change over time

#### 5 4 Resource Negotiation and Graph Search

Resource negotiation between teams employs distributed bidding techniques using remote autonomous agents and is robust to communication failures through pseudo-centralization. Remote Autonomous Agents allow each resource consumer to dispatch intelligent agents to take up residence and execute on computers at remote resource supplier and consumer nodes.

These agents bid against others on resources that may be available at those nodes and the (possibly constrained) highest bidder obtains the resource, or the resource is divided in proportion to the bids. The agents perform the communication and negotiations, and inform their owners of resource availability and allocations.

The environmental partitioner/central planner (~~Section 2~~) will *may* establish the governing parameters of the bidding. It will create the initial team groupings and task representations, assign costs to resources and awards for task completion, and establish a normalization scheme for the  
 5 bidding.

The actual bidding and assignment of resources may be carried out using a combination of several auction-based algorithms. The "assignment problem" of associating a stream of observations from multiple sensors to target tracks in real-time has been addressed and largely solved by a  
 10 variety of algorithms.

An exhaustive solution (e.g., the Munkres algorithm) would require enumeration of all combinations of sets of pairings, which, for a large number of items, would be computationally infeasible ~~[2]~~. Much work has been done to reduce the computational time for real-time results. The  
 15 "Hungarian method" ~~[8]~~ is an example of a way to reduce computational complexity. The "JVC algorithm" is an example of a method that is based on a combination of "auction" and "modified Munkres", ~~[1, 3]~~. "Lagrangian relaxation" ~~[9, 10]~~ has been used to support multidimensional assignment.

The "auction" consists of several rounds of bidding. In the first  
 20 round, supply items (rows) are offered at different prices to the first choice (highest profit) column on the basis of cost and the lower profit that would be obtained from the second choice. This results in an initial assignment. Successive rounds of bidding may change the initial assignments, but, to

prevent endless oscillation and assure that there will not be infinite rounds of bidding, an epsilon factor is added to the bid at each round. Larger values for epsilon yield faster results but reduce overall performance.

Some methods dynamically vary the value of epsilon, to achieve initial

5 results rapidly, but then repeat the process to improve the quality of the assignments. It is also possible that the negotiation scheme may change dynamically based on changing environmental conditions such as reduced communication capability. The procedures above have been described as a centralized solution, however an advantage of auction-based methods is

10 that they are highly parallelizable, and may be implemented by semi-independent computations on processors at each supplier and consumer entity. So long as each processor bids according to the same algorithm and the same relative value for price and cost, based on norms and instructions from higher authority, they need only exchange bids for the

15 system to work. A kind of pseudo-centralized planning will result, where the use of physically distributed ANT agents employing communications to negotiate according to the rules of the more centralized auction algorithms will provide the coordination and performance benefits of centralization with the speed and robustness of distributed processing.

20 Successful negotiations will result in logical links between the modular PN graphs of the various teams. The proper links and additional structures for performing deadlock avoidance will be automatically synthesized using techniques from supervisory control (~~see Section 3.2~~).

The reliance of one task upon the completion of another is similar to the reliance on a particular resource. Thus completed tasks may also be handled as items for negotiation, and the negotiating teams will dynamically create a hierarchy of inter-dependencies and cooperation. In  
 5 this way, higher-level teams will result as an emergent phenomenon of the ANT approach. Fig. 5 provides an illustration of an ANT hierarchy *5001*.

Once negotiations for resources have been settled and the distributed PN graph is established, intelligent agents will perform an accurate and efficient search of the PN graph to find paths that lead to a  
 10 solution. "Good enough, fast enough" solutions are required for planning routes through the graph, from the initial conditions to the objectives, that attempt to minimize costs and maximize rewards. A number of novel computational geometry techniques have been developed that involve intelligent partitioning of the search space ~~[2, 12]~~. This partitioning  
 15 allocates probabilities of high and low reward, allowing automatic pruning of undesirable (low probable reward) portions of the graph. The search is further accelerated by the supervisory control structures incorporated in the PN graph. These automatic resource management and deadlock avoidance structures will have already pruned infeasible solutions from the  
 20 reachable search space of the graph.

The cooperation among teams, negotiation for resources, and search for paths to the mission objectives are dynamic, capable of responding to changes in the problem domain and adapting the resultant

ANT behavior. Resources may be lost or destroyed, or other forms of attrition may occur that remove subtasks from the distributed PN graph. Alternately, new tasks may be introduced into the mission. Teams may also detect new information about the environment, such as determining  
5 the presence of a previously unknown threat. Any of these events will automatically initiate new rounds of negotiation between teams, and new paths to the mission objectives will be developed. The ANT architecture (see Fig. 1) allows these events to be handled autonomously by the individual teams, without requiring communication with a central authority.

10 The environmental partitioner/central planner may also become involved in dynamically responding to changing situations. If new capabilities become available for the mission, the planner will compose these potential tasks and resources and indicate that a new round of negotiation and search should begin. If sensor and communications  
15 capabilities permit, the planner may also re-evaluate the current mission situation and introduce strategic changes into ANT behavior. Relaying new resource costs and objective rewards will induce new negotiations that account for the changed priorities.

## **5 Implementation Notes**

20 The ANT architecture is an interdisciplinary solution to the problem of autonomous teams employing scalable resource negotiations. The areas of computational geometry and graph search bring novel routines to



partition application-specific problem domains, compose mission objectives from modular subtask descriptions, and intelligently assign resource costs and objective rewards. ANT representations benefit from cutting-edge, scalable, resource-management techniques from the area of discrete event systems. Advances in supervisory control theory bring revolutionary, integrated deadlock avoidance techniques, required to improve the quality of ANT solutions.

There are a number of different ways to handle the engineering specifics of the interaction between agents, including Java Applets, the Task Network Architecture, and the Object Management Group's (OMG) Common Object Request Broker Architecture (CORBA). The Modular Semi-Automated Forces (ModSAF) simulation environment provides an excellent tool kit for simulating autonomous teammates in a variety of real-world scenarios.

## REFERENCES

- [1] D. P. Bertsekas, "The Auction Algorithm: A Distributed Relaxation Method for the Assignment Problem", *Annals of Operations Research* 14 (1988) 105-123
- [2] D. Chen, R. Szczerba, and J. Urhan Jr. "A Framed-Quadtree Approach for Determining Euclidean Shortest Paths in a 2-D Environment," *IEEE Transactions on Robotics and Automation*, vol. 13, no. 5, pp. 668-681, October 1997.
- [3] O. E. Drummond, D. A. Castanon, M. S. Bellovin, "Comparison of 2-D Assignment Algorithms for Sparse, Rectangular, Floating Point, Cost Matrices," *Journal of the SDI Panels on Tracking*, Institute for Defense Analyses, Alexandria, VA, 4/1990 4-81 - 4-97

- [4] L. Holloway, B. Krogh, and A. Giua, "A Survey of Petri Net Methods for Controlled Discrete Event Systems", *Discrete Event Dynamic Systems: Theory and Applications*, vol. 7, no. 2, pp. 151-190, April, 1997.
- 5 [5] M. Iordache, *Deadlock Prevention in Discrete Event Systems Using Petri Nets*, Masters Thesis, Department of Electrical Engineering, University of Notre Dame, Notre Dame, IN., 1999
- [6] H. W. Kuhn, "The Hungarian Method for the Assignment Problem", *Naval Research Logistics Quarterly* 2 (1955) 83-97
- 10 [7] J. Moody and P. Antsaklis, *Supervisory Control of Discrete Event Systems Using Petri Nets*, Kluwer Academic Publishers, 1998
- [8] T. Murata, "Petri Nets: properties, Analysis, and Applications", *Proceedings of the IEEE*, vol. 77, no. 4, pp. 541-580, 1989
- 15 [9] A. B. Poore, N. Rijavec, M. Liggins, V. C. Vannicola, "Data Association Problems Posed as Multidimensional Assignment Problems: Problem Formulation", *SPIE Proceedings*, Vol 1954 (1993) 552-563
- [10] A. B. Poore, N. Rijavec, T. N. Barker, M. Munger, "Data Association Problems Posed as Multidimensional Assignment Problems: Numerical Simulations", *SPIE Proceedings*, Vol 1954 (1993) 564-573
- 20 [11] P. Ramadge and W. Wonham, "The Control of Discrete Event Systems", *Proceedings of the IEEE*, vol. 77, no. 1, pp. 81-97, 1989.
- [12] H. Samet. "An Overview of Quadtrees, Octrees, and Related Hierarchical Data Structures," *NATO ASI Series*, F40:51-68, 1985.

### Detailed Description

Reference is now made to Figs. 6 and 7 that illustrate hardware  
 25 employed in practicing the invention. Fig. 6 illustrates a distributed data  
 processing system<sup>10</sup> in accordance with the invention for purposes of  
 controlling allocation of resources employed in performing various tasks.  
 In the embodiment illustrated, the system includes a communications  
 network 100 for purposes of passing messages between various

computers connected to the network. The computers are sometimes referred to as "machines". As shown in Fig. 6, several computers 102, 104, 106, 108, 110 and 112 are shown as being connected to the network 100. These computers house software algorithms, sometimes

5 referred to as programs or routines. One of the computers runs the central authority (strategic layer) and the others run the autonomous agents (tactical layers). For purposes of illustration only, computer 102 ~~runs~~ <sup>may run</sup> the central authority and the other computers <sup>may</sup> run agents. If desired, two agents may be run on the same computer. The network may be any type

10 of network that allows the computers to send and receive messages, however, the preferred network takes the form of a local area network (LAN) or the internet, using the transmission control protocol/internet protocol (TCP/IP). ~~It is intended that~~ <sup>may</sup> the agents operate at remote locations, apart from the central authority.

15       The central authority and the agents may be run on computers having similar capabilities. An example of one of the computers, such as computer 104, is illustrated in Fig. 7. As shown there, the computer 104 conventionally includes a processor 120, a memory in the form of a random access memory (RAM) <sup>122</sup> 122. The RAM <sup>122</sup> contains an operating

20 system 124 and various applications 126 including a user interface 128, a communication interface 130 and logic and algorithms 132. The computer <sup>104</sup> 104 also includes a non-volatile memory 134 and suitable communications hardware 136. It is to be appreciated that the programs for the central

authority and the agents may be run on various computers which may be structured similar to or different from computer 104 as illustrated in Fig. 7.

Reference is again made to Fig. 1 which presents a high level

<sup>1001</sup> description of the distributed algorithm performed by the central authority

5 and the autonomous agents. The upper half of the figure represents the

strategic layer <sup>1100</sup> and this <sup>may be</sup> is performed by a program running on a single

machine employed for the central authority. The bottom half of the figure

represents the tactical layer <sup>1200</sup> and this is likely to be performed by programs

running on multiple machines, the autonomous agents. Communication

10 between the various entities is handled by passing messages over the network 100 (Fig. 6).

Reference is now made to Fig. 8 which illustrates the various types

of data supplied as inputs <sup>(A, B, C, D, E)</sup> to the central authority (CA) and the various

types of data provided as outputs <sup>(F, G, H, I)</sup> from the central authority (CA). The

15 inputs are indicated by the arrows A, B, C, D and E and the outputs are

indicated by the arrows F, G, H and I. The data supplied to the inputs A-D

may be provided by <sup>a</sup> suitable data source, such as another machine, or

perhaps may be entered at a keyboard of the computer <sup>(Fig. 6)</sup> 102 that runs the

central authority (CA). The data that is supplied at input E is received from

20 the agents in this system. There are different types of data being applied

to the inputs and for example the data supplied to input A, as indicated by

the box 150, includes modular task representations including Petri Net

(PN) task components. This may also be considered as data representing Petri Net models of tasks which are mapped to task types. As shown in box 152, the data supplied to input B represents input conditions including the number and types of resources, the location of resources, the number and types of task capabilities, the location of task implementers and mapping between task components and PN modules. As indicated at box 154, the data supplied to input C includes mission constraints including linear inequalities. As shown in Box 156, the data supplied to input D includes mission objectives including completed tasks with relative values assigned. The data being supplied to input E is indicated by box 158. This includes dynamic updates from the agents including local connections and dependencies, the remaining resources, and the task status.

Box 160 in Fig. 8 represents the type of data provided at output F of the central authority CA. This data is directed to agent initial conditions including PN structure, PN initial conditions, task and resource mappings and the number and type of resources. The central authority generates a graph (PN graph) associated with each agent and wherein the graph represents for the associated agent what resources that agent has and what task or tasks that agent may perform.

Box 162 in Fig. 8 indicates the type of data provided at output G of the central authority. This data includes resource usage cost and task completion reward.

Box 164 in Fig. 8 illustrates the type of data provided at output H of the central authority. This includes revised tasks and resource mappings. The data from outputs F, G and H of the central authority CA are supplied to each of the agents AG-1 through AG-n as will be appreciated with  
 5 reference to Fig. 10 to be described hereinafter.

Box 166 indicates the type of data provided by output I and this includes user feedback. This, for example, may be a video display at the computer that runs the central authority so that the operator may receive a message.

10 All of the autonomous agents <sup>maybe</sup> ~~are~~ essentially the same. Reference is now made to Fig. 9 which illustrates agent AG-1, it being understood that the description is equally applicable to the other agents. *AG-2 .... AG-n.*

Agent AG-1 has inputs J, K, L, M and N and outputs O, P, Q and R. The inputs J, K and L are received from the central authority CA. These  
 15 inputs include the agent initial conditions shown in block 180 and applied to input J. The agent initial conditions include PN structure, PN initial conditions, task and resource mappings and the number and type of resources. Block 182 shows the data being applied to input K of the agent. This block <sup>182</sup> includes resource usage costs and task completion reward.  
 20 Block 184 shows the data supplied to the input L and this includes revised task and resource mappings. Block 186 shows the data that is supplied to input M. This block <sup>186</sup> illustrates the incoming negotiating messages received

from other agents. The incoming negotiation messages includes bids, offers and acceptances. Block 188 shows the data that is supplied to the input N and this data is received from other agents and includes external agent dependency link messages.

5            Fig. 9 also illustrates the data supplied at the various outputs O, P, Q and R of agent AG-1. Block 190 shows the negotiation messages provided at output O of agent AG-1 and these messages are forwarded to other agents. These messages include bids, offers and acceptances. Block 192 illustrates data provided at output P of agent AG-1. These  
10    messages are forwarded to other agents at their inputs 188. These messages at output P include dependency link messages to external agents. Block 194 shows data provided at output Q of agent AG-1. This includes updates to the central authority CA including local connections and dependencies, remaining resources and task status. This is supplied  
15    at input E of the central authority CA (Fig. 8). Block 196 shows the data supplied at the output R of agent AG-1 and this includes user feedback. This could be a message or other data and for example may be supplied to a machine controlled by the agent.

Reference is now made to Fig. 10 which illustrates a flow diagram  
20    (not a wiring diagram) showing the manner in which the central authority outputs F, G, H and I are supplied to the inputs J, K and L, of the various

agents and the manner in which the outputs O, P and Q of the various agents are supplied to the other agents as well as to the central authority *CA.*

Reference is now made to Figs. 11 and 12 which together present a flow diagram of the central authority CA. Part 1 of the central authority is  
5 illustrated in Fig. 11 and Part 2 is illustrated in Fig. 12.

The program commences at step 200 and advances to step 202. In step 202, the program constructs a PN model of all resources and tasks based on data that has been entered at its inputs A and B (Fig. 8) and this includes Petri Net models of tasks mapped to task types, number and type  
10 of resources and types and number of tasks. The ~~procedure~~ *program* then advances to step 204.

In step 204, the ~~routine~~ *program* constructs supervisory control structure to enforce constraint dependencies and this is based on the ~~previous~~ *202,* step as well as data that was supplied to input C (Fig. 8) including mission  
15 constraints ~~including~~ *with* linear inequalities in terms of resources and task results representing mission constraints. The ~~procedure~~ *program* advances to step 206 during which all agents are marked as not initialized. The ~~procedure~~ *program* then advances to step 208.

In step 208, data is obtained regarding mission objectives described  
20 in terms of rewards associated with task results and basic resource costs. During this ~~step~~ *208,* penalties are assigned for resource consumption and rewards are assigned for all subtask ~~results~~ *results*. Penalties correspond to real



world quantities such as price, time, labor or availability of resources.

Rewards correspond to the value of completing a task. It is possible that only one task, that representing the completed over all objective, will have a reward. The autonomous agents will deduce new reward values that

- 5 lead to the completion of the objective through their negotiation process.

The ~~procedure~~ <sup>program</sup> then advances to step 210.

In step 210, all agents are marked as not updated. The ~~procedure~~ <sup>program</sup> then advances to step 212.

- 10 In step 212, a determination is made as to whether any agents are not initialized. If the answer is yes, the ~~procedure~~ <sup>program</sup> advances to step 214.

~~In~~ At step 214, data is received representing the locations of potential agent processors and locations of resources and potential task implementers. In this step the ~~routine~~ <sup>214, program an</sup> decomposes overall PN model for distribution among individual agents. The ~~procedure~~ <sup>program</sup> then advances to step 215 (see Fig. 12).

- 15 In step 215, a determination is made as to whether any agents are not initialized. If the determination is yes, the ~~procedure~~ <sup>program</sup> advances to step 216. In this step, <sup>216,</sup> for a non-initialized agent, the ~~routine~~ <sup>program</sup> sends its PN structure and initial conditions, task and resource mappings and the number and type of resources. The ~~procedure~~ <sup>program</sup> advances to step 218 at
- 20 which the agent is marked as initialized. Then the ~~procedure~~ <sup>program</sup> advances to step 215. Since the determination at step 215 will now be negative, the ~~procedure~~ <sup>program</sup> will advance to step 220. Step 220 may also be reached from

step 212 (Fig. 11) if a negative determination was made at that step<sup>212.</sup> In step 220, a determination is made as to whether there are any non-updated agents. If the answer is yes, the ~~procedure~~<sup>program</sup> advances to step 222. In this step<sup>222,</sup> for a non-updated agent, the ~~routine~~<sup>program</sup> sends resource usage costs and task completion reward data and the ~~procedure~~<sup>program</sup> advances to step 223. In step 223, the agent is marked as being updated and the ~~procedure~~<sup>program</sup> advances to step 220. Since the determination is now negative at step 220 the ~~procedure~~<sup>program</sup> advances to step 224.

In step 224, the ~~routine~~<sup>program</sup> receives any incoming agent messages and then advances to step 226. In this step<sup>226,</sup> the ~~procedure~~<sup>program</sup> provides user feedback such as that discussed hereinbefore with reference to block 166 (Fig. 8) relative to the output I of the central authority CA. The ~~procedure~~<sup>program</sup> then advances to step 228.

In step 228, a determination is made as to whether the mission is complete. If not, the procedure returns to step 224 and repeats steps 224, 226 and 228. When the determination at step 228 is yes and the mission has been completed, the ~~procedure~~<sup>program</sup> is done as indicated by the "done" step 230.

### Tactical Layer/Autonomous Agents

Attention is now directed to Figs. 13 and 14 which respectively represent Part 1 and Part 2 of the program<sup>1300</sup> for the autonomous agents.

This program<sup>1300</sup> commences at step 300 and advances to step 302. In step 302, data is supplied from the central authority CA relative to the set up conditions. Further in step 302, a) determination is made as to whether initialization data has been received. This data includes the set up from the central authority including the PN structure, PN initial conditions, task and resource mappings and number and type of resources. If the data has not been received, then the ~~procedure~~ <sup>program</sup> repeats. If the data has been received, the ~~procedure~~ <sup>program</sup> advances to step 304.

In step 304, the ~~procedure~~ <sup>program</sup> provides setup of internal PN representation ~~and this is based on the decision from step 302 as well as that from step 310 and step 338 (Fig. 14) to be described in detail hereinafter.~~ The ~~procedure~~ <sup>program</sup> advances to step 306. In step 306, the ~~procedure~~ <sup>program</sup> calculates deadlock avoidance structures and proceeds to step 308. In step 308, outgoing agent dependency links are forwarded and the ~~procedure~~ <sup>program</sup> advances to step 310. In step 310, a determination is made as to whether any incoming agent dependency link messages have been received. If yes, then the procedure returns to step 304 and steps 304, 306 and 308 are repeated.

If the determination in step 310 is no, then the ~~procedure~~ <sup>program</sup> advances to step 312 during which a determination is made as to whether cost data has been received. This is data from the central authority which is an update dealing with resource usage cost and task completion rewards. If

the determination in step 310 is negative, the ~~procedure~~<sup>program</sup> repeats. If the determination at step 312 is affirmative, the ~~procedure~~<sup>program</sup> advances to step 314 (Fig. 14).

In step 314, the agent sends updates to the central authority including local connections and dependencies, remaining resources and task status. The ~~procedure~~<sup>program</sup> then advances to step 316. Step 314 is not a blocking step. If the agent cannot communicate with the central authority it will still advance to step 316.

In step 316, the agent calculates the desired output offer costs and the ~~procedure~~<sup>program</sup> advances to step 318. In step 318, the agent forwards outgoing offers and the ~~procedure~~<sup>program</sup> advances to step 320.

In step 320, a determination is made as to whether the agent needs additional resources to complete the task. If not, the ~~procedure~~<sup>program</sup> advances to step 322 at which the agent receives incoming bids. <sup>In</sup> At step 322, the agent will increase the reward value associated with completing a task to match the value of the highest incoming bid for that task completion. If the answer to the determination in step 320 is affirmative, the agent needs to negotiate with other agents to obtain resources. The ~~procedure~~<sup>program</sup> advances to step 324 during which the agent calculates the desired resource bid costs and the procedure advances to step 326.

In step 326, the agent forwards outgoing bids to other agents and advances to step 328 in which the agent receives incoming offers from

other agents. The ~~procedure~~ <sup>program</sup> then advances to step 322 in which the agent receives incoming bids and the ~~procedure~~ <sup>program</sup> advances to step 330.


In step 330, the agent determines whether there have been any acceptable offers or bids. Acceptable offers must be equal <sup>to</sup> or less than the current reward value for completing the given task. Acceptable bids must equal or exceed the cost to obtain the necessary resources to complete the task. Is there are no acceptable offers or bids, the program ~~if not, the procedure~~ advances to step 332. In step 332, the agent receives incoming acceptances. If the determination in step 330 is affirmative, the ~~procedure~~ <sup>program</sup> advances to step 334 during which the agent provides outgoing acceptances.


After step 332, the ~~procedure~~ <sup>program</sup> advances to step 336. In ~~the~~ step <sup>336</sup>, feedback is provided to the user in the nature described before with reference to output R of the agent AG-1. The ~~procedure~~ <sup>program</sup> then advances to step 338.

In step 338, a determination is made as to whether there are any new acceptances. If yes, the ~~procedure~~ <sup>program</sup> returns to step 304 and steps 306-336 are repeated. (Fig. 336)

If the answer in determination 338 is ~~negative~~ <sup>no</sup>, the ~~procedure~~ <sup>program</sup> advances to step 340. In ~~this~~ <sup>340</sup> step, the agent determines whether any resources are needed to complete the task. If yes, the ~~procedure~~ <sup>program</sup> returns to step 324 during which the agent calculates the desired resource bid costs and steps 326-340 are repeated.

If the determination in step 340 is ~~negative~~ <sup>no</sup>, the ~~procedure~~ <sup>program</sup> advances to step 342. In ~~this~~ <sup>342,</sup> step the agent searches the PN graph for a path to task completion. The ~~procedure~~ <sup>program</sup> then advances to step 344. In ~~this~~ <sup>344,</sup> step the agent performs the task and the ~~procedure~~ <sup>program</sup> advances to step 346.

- 5 In step 346, the agent provides the user with feedback such as that with reference to output R of the agent AG-1 described previously. 

 After step 346, the ~~procedure~~ <sup>program</sup> advances to step 348. During ~~this~~ <sup>348,</sup> step the agent updates the central authority with the task status and the ~~procedure~~ <sup>program</sup> advances to step 350.


- 10 In step 350, the agent determines whether the task is complete. If so, the ~~procedure~~ <sup>program</sup> is complete as indicated by step 352 for done. If in step 350 the task was not complete, the ~~procedure~~ <sup>program</sup> returns to step 344 and steps 344-350 are repeated.

### Summation

- 15 ~~This is a process for establishing~~ <sup>An architecture in accordance with the present invention establishes,</sup> from the top down a framework for different operating agents each capable of performing tasks and/or holding resources, each task requiring the use of resources. Members of teams ~~may~~ <sup>may</sup> include computers, other cooperating agents or people operating computers. Certain resources may be shared with, or allocated to, another agent in order to perform their tasks. The strategic layer assigns costs and rewards for consuming resources and completing tasks, and it ~~can~~ <sup>may</sup> compose subtasks into higher level tasks that lead toward the completion
- 20

of mission goals. At the tactical level, the model that represents the task flow <sup>may be</sup> ~~is~~ augmented to include the dependencies that are associated with resource consumption. The model is augmented to assure that paths from start to finish are achievable, i.e., capable of completion without achieving a state of deadlock. The tactical layer goes on to include negotiation between different agents for resources ~~they hold~~ based on task completion and the cost of resources. After negotiation is complete, a path is searched from starting point to achievement of mission goals.

Although the invention has been described in conjunction with the preferred embodiments, it is to be appreciated that various modifications may be made without departing from the spirit and scope of the invention as defined by the appended claims.











Fig 2

3002



(b)

Fig 3(b)



(a)

Fig 3(a)

3001

4002  
↓




Fig 4(b)

4001  
→




Fig 4(a)

5001






Fig. 6 Network of central authority and agent machines








Fig. 9 Tactical Layer Autonomous Agents - Inputs and Outputs






Fig. 10 Interconnections of Central Authority and Autonomous Agents





Fig. 1) // Algorithm: Strategic Layer / Central Authority - Part 1



CA

Fig. 12 Algorithm: Strategic Layer / Central Authority - Part 2




Fig. 13 Algorithm: Tactical Layer / Autonomous Agents - Part 1

1300

